



SEEPAGE AND GROUNDWATER FLOW IN PLAXIS IMPORTANT NOTES

- PIGSO LEARNING



DEFINITION: SEEPAGE AND GROUNDWATER FLOW MODELLING IN PLAXIS

Seepage and groundwater flow analysis in PLAXIS simulates the movement of water through soils and its interaction with geotechnical structures.

PLAXIS provides steady-state seepage (time-independent) and transient seepage (time-dependent) analyses, using boundary conditions, soil permeability, and coupled flow-deformation (consolidation) to capture realistic hydro-mechanical responses.

Important Notes

Q1. What soil property is most important for seepage analysis in PLAXIS, and why?

The most important soil property is hydraulic conductivity (permeability, k) because it governs the ease of water flow. Flow velocity is given by Darcy's Law:

$$v = \frac{q}{n} = -\frac{k}{n} \cdot \nabla h$$

where

- q = discharge per unit area,
- n = porosity,
- h = hydraulic head.

Soils with higher k (such as sand and gravel) allow rapid seepage, while clays (with low k) store water and develop excess pore pressures. Correct k values are vital for realistic seepage results.

Q2. How is a phreatic surface defined and used in PLAXIS models?

Answer:

The phreatic surface is the water table line, above which soil is unsaturated and below which pore pressures exist. In PLAXIS, users define it through initial head levels or flow boundaries. Below the phreatic surface, pore water pressure is calculated as:

$$u = \gamma_w \cdot h_w$$

where

- u = pore pressure,
- γ_w = unit weight of water,
- H_w = depth below phreatic surface.

This definition ensures correct effective stress calculation:

$$\sigma' = \sigma - u$$

This directly influences slope and excavation stability.

Q3. Explain the difference between steady-state and transient (time-dependent) seepage analysis.

Answer:

- **Steady-state seepage:** Hydraulic heads and pore pressures remain constant with time. It is solved using:

$$\nabla \cdot (k \cdot \nabla h) = 0$$

This applies to long-term groundwater flow after equilibrium is reached.

- **Transient seepage:** Pore pressures vary with time due to rainfall, pumping, or drawdown. The governing equation includes storage effects:

$$\nabla \cdot (k \cdot \nabla h) = S_s \cdot \frac{\partial h}{\partial t}$$

where S_s = specific storage, t = time.

PLAXIS transient mode is critical for short-term stability problems such as rapid reservoir drawdown.

Q4. What is Darcy's Law, and how is it implemented in PLAXIS?

Answer:

Darcy's Law defines groundwater flow in porous media:

$$q = -k \cdot \nabla h$$

where

- q = specific discharge (m/s),
- k = hydraulic conductivity,
- ∇h = hydraulic gradient.

In PLAXIS, this law is applied in seepage and coupled analyses to compute water velocities and pore pressures. The law also accounts for anisotropy (different K_x , K_y in different directions), which is essential in stratified soils.

Q5. Why is modelling boundary conditions crucial for seepage simulation?

Answer:

Boundary conditions define water inflow, outflow, or no-flow in the model. Common options:

- **Head boundary:** fixes total head h ,
- **No-flow boundary:** $q=0$, impermeable,
- **Seepage face:** pore pressure cannot exceed atmospheric pressure.

Incorrect boundaries can lead to unrealistic pore pressures and stress predictions. For example, failure to define a proper drainage boundary may overestimate uplift pressures beneath an excavation.

Q6. How does PLAXIS couple deformation and seepage in consolidation analysis?

Answer:

PLAXIS couples flow and deformation using Biot's consolidation theory:

$$\nabla \cdot (k \cdot \nabla h) + \frac{\partial \varepsilon_v}{\partial t} = S_s \cdot \frac{\partial h}{\partial t}$$

Where ε_v is volumetric strain.

This captures how soil volume changes with pore pressure variation. For example, in soft clay foundations, excess pore pressures gradually dissipate, causing time-dependent settlements (primary consolidation).

Q7. What are typical applications of seepage and groundwater flow modelling in PLAXIS?

Answer:

- **Dams & levees** → seepage, piping, uplift stability.
- **Tunnels & excavations** → groundwater inflow predictions.
- **Slopes** → rainfall-induced failures or drawdown effects.
- **Drainage & cutoff wall design** → optimising flow reduction measures.

Each case relies on correct permeability, boundary conditions, and coupled analysis to represent real behaviour.

Q8. How do water pressure changes influence soil stability in excavations or slopes?

Answer:

Pore pressure affects effective stress:

$$\sigma' = \sigma - u$$

where σ' = effective stress, σ = total stress, u = pore pressure.

- **Increase in u reduces σ'** → loss of shear strength, slope instability, or basal heave in excavations.
- Rapid drawdown reduces water load, but pore pressures inside the soil remain high, creating instability.

Thus, correct seepage modelling is essential for safety checks.

Q9. Which PLAXIS analysis modes should be used for seepage problems?

Answer:

- **Alternating vortices detach from the cylinder** → Kármán vortex street.
- Occurs when $Re > 47$.
- **Causes oscillating lift and drag forces** → can induce vibrations in tall chimneys, offshore structures, and bridge piers.

Q10. What is the pressure coefficient (C_p) and how is it calculated?

Answer:

- **Cutoff/diaphragm walls** → reduce permeability (k) around excavation, lowering seepage.
- **Dewatering wells or drainage blankets** → reduce pore pressures, ($u = \gamma_w h_w$) stabilising excavation base.

These countermeasures are modelled by modifying soil permeability or adjusting boundary conditions in PLAXIS.



Thanks for growing your skills with PIGSO LEARNING!

Follow us for more technical tips, expert insights, and real-world geotechnical guidance.

Drop a comment if you like this post, and suggest topics you'd like us to cover next.

Got feedback or want to connect? We'd love to hear from you!

— Team PIGSO LEARNING

Connect with PIGSO LEARNING

